

AQUA PRIMER

P 01953 528060

E info@lunaplaster.co.uk

W www.lunaplaster.co.uk

PRODUCT DESCRIPTION

Aqua Primer is a single component water-based primer for porous substrates.

Only to be used on wall systems.


MATERIAL FEATURES

- Touch dry in 15-30 minutes
- Suitable for porous substrates such as gypsum-based products
- Single Component
- Can be force dried

KEY INFORMATION



USE NEAT



TECHNICAL DATA

Product type: Primer

User time: Unlimited

Appearance: White liquid

Chemical Nature: Water-based primer

Shelf Life: 12 months

Consumption: 60-80g/m²

AQUA PRIMER APPLICATION INSTRUCTIONS

1. SURFACE PREPERATION

The substrate must be firm, dimensionally stable, capable of bearing loads and free of loose debris, dust, oil, grease, rubber marks and other substances that could interfere with adhesion.

Substrates must have reached their moisture balance and must also be protected against moisture penetration from the reverse side, including during use.

Prepare the substrate by suitable means, e.g., sanding or diamond grinding.

2. APPLICATION

Roll on with microfibre roller until the substrate is saturated, with no visible dry spots.

It may be necessary to apply more than one layer.

3. SPECIAL PRECAUTIONS

- Keep out of reach of children
- Clean tools with water
- Wear PPE