

EARTH PLASTER (NATURAL)

P 01953 528060

E info@lunaplaster.co.uk

W www.lunaplaster.co.uk

PRODUCT DESCRIPTION

Trowel applied clay. EARTH PLASTER (NATURAL) is used as a base and topcoat in the Earth Plaster system.


MATERIAL FEATURES

- Eco friendly clay
- Easy application
- Internal
- Fast drying – can be force dried

KEY INFORMATION



MIX TIME
3 MINUTES



WORKING
TEMP



TROWEL
APPLICATION



FROST FREE



SHELF LIFE
12 MONTHS



WEAR
GOGGLES



WEAR
GLOVES

TECHNICAL DATA

Product type: Clay

User time: Unlimited

Appearance: Dry clay/powder

Shelf Life: 12 Months (when stored in a dry area)

Thickness: 1-1.5mm per layer

EARTH PLASTER (NATURAL) APPLICATION INSTRUCTIONS

1. SURFACE PREPARATION

Ensure the substrate is dry, contaminant free and well prepared.. Make sure all debris has been hoovered off to leave a clean surface to achieve the best adhesion.

2. APPLICATION

Apply EARTH PLASTER (NATURAL) using a stainless-steel trowel to desired effect and finish at the correct thickness.

Consumption	
Mesh Wall:	
All Coats	1 - 1.1kg/m ²
Fast wall/Super-fast wall:	
First Coat	700g - 800g/m ²
Second Coat	1 - 1.1kg/m ²
Water	
Stiff Grade	2 - 2.5 Litres per 10kg
Wet Grade	2.9 - 3.2 Litres Per 10kg

3. SPECIAL PRECAUTIONS

- For professional use only
 - Store in a dry, warm area. Do not allow to get wet or damp.
 - Do not apply below +5c or above +25c.
 - Keep out of reach of children.
 - Dispose of waste in accordance with current legislation
-

4. CLEANING OF TOOLS

Tools can be cleaned using fresh water and a soft brush. Ensure any mixing equipment has been unplugged before cleaning.