

## EARTH PLASTER (REFINED)

**P** 01953 528060

**E** info@lunaplaster.co.uk

**W** www.lunaplaster.co.uk

### PRODUCT DESCRIPTION

Trowel applied clay. EARTH PLASTER (REFINED) is used as a topcoat in the Earth Plaster system.


### MATERIAL FEATURES

- Eco friendly clay
- Easy application
- Internal
- Fast drying – can be force dried

### KEY INFORMATION



MIX TIME  
3 MINUTES



WORKING  
TEMP



TROWEL  
APPLICATION



FROST FREE



SHELF LIFE  
12 MONTHS



WEAR  
GOGGLES



WEAR  
GLOVES

### TECHNICAL DATA

Product type: Clay

User time: Unlimited

Appearance: Dry clay/powder

Shelf Life: 12 Months (when stored in a dry area)

Thickness: Less than 1mm per layer

---

# **EARTH PLASTER (REFINED) APPLICATION INSTRUCTIONS**

---

## **1. SURFACE PREPARATION**

---

Ensure the substrate is dry, contaminant free and well prepared. Make sure all debris has been hoovered off to leave a clean surface to achieve the best adhesion.

---

## **2. APPLICATION**

---

Apply EARTH PLASTER (REFINED) using a stainless-steel trowel to desired effect and finish at the correct thickness.

Consumption: 130g/m<sup>2</sup>

Water: 3 - 3.5 litres per 5kg for stiff grade

4.5 - 5 litres per 5kg for wet grade

---

## **3. SPECIAL PRECAUTIONS**

---

- For professional use only
  - Store in a dry, warm area. Do not allow to get wet or damp.
  - Do not apply below +5c or above +25c.
  - Keep out of reach of children.
  - Dispose of waste in accordance with current legislation
- 

## **4. CLEANING OF TOOLS**

---

Tools can be cleaned using fresh water and a soft brush. Ensure any mixing equipment has been unplugged before cleaning.