

MONO SEALER

P 01953 528060

E info@lunaplaster.co.uk

W www.lunaplaster.co.uk

PRODUCT DESCRIPTION

Mono Sealer is a single component, cross linking, polyurethane sealer.

MATERIAL FEATURES

- Flat matt
- Single component
- UV resistant
- Touch dry in 1-2 hours
- Can be force dried

KEY INFORMATION



USE
NEAT



TECHNICAL DATA

Product type: Sealer

Appearance: White liquid

Shelf Life: 12 months

Consumption: 120g – 150g per m²

User time: Unlimited

MONO SEALER APPLICATION INSTRUCTIONS

1. SURFACE PREPARATION

The finish coat must be firm, dimensionally stable, capable of bearing loads and free of loose constituents, dust, oil, grease, rubber marks and other substances that could interfere with adhesion.

2. APPLICATION

Using a 12inch microfibre roller apply in a cross-hatch technique ensuing roller lines are minimized.

Consumption rate: 120g-150g /m²

3. SPECIAL PRECAUTIONS

- For professional use only
 - Do not apply below +5°C or above +25°C
 - Keep out of reach of children
 - Dispose of waste in accordance with current legislation
-

4. CLEANING OF TOOLS

Clean tools, equipment, and any splashed material immediately with water while still fresh. Take suitable protective and waste disposal measures when cleaning.