

## MONO SMOOTH

**P** 01953 528060

**E** info@lunaplaster.co.uk

**W** www.lunaplaster.co.uk

### PRODUCT DESCRIPTION

One component thixotropic paste for pore-filling & creating effects onto microcement, can be used with pigments or on its own.

### MATERIAL FEATURES

- Gloss
- Slip-resistant
- UV resistant
- Water vapor diffusion capable

### KEY INFORMATION



USE  
NEAT



### TECHNICAL DATA

Product type: Sealer

User time: (+20°C) 60 minutes

Appearance: Clear liquid

Chemical Nature:

Shelf Life: 12 months

Consumption: 70g – 80g per m<sup>2</sup>

---

# **MONO SMOOTH APPLICATION INSTRUCTIONS**

---

## **I. SURFACE PREPARATION**

---

The finish coat must be firm, dimensionally stable, capable of bearing loads and free of loose constituents, dust, oil, grease, rubber marks and other substances that could interfere with adhesion.

---

## **2. APPLICATION**

---

Apply the material to the surface and trowel to the required finish.

Consumption rate: 70g – 80g /m<sup>2</sup>

---

## **3. SPECIAL PRECAUTIONS**

---

- For professional use only
  - Do not apply below +5°C or above +25°C
  - Keep out of reach of children
  - Dispose of waste in accordance with current legislation
- 

## **4. CLEANING OF TOOLS**

---

Clean tools, equipment, and any splashed material immediately with water while still fresh. Take suitable protective and waste disposal measures when cleaning.